

Manual Pull Station

- **Model** : CL-202
- **Application** : Indoor
- **Adopted voltage** : DC ~ 18 ~ 28V (DC-24)
- **Adopted current** : 100 mA
- **Function** : Push Button Emergency, Phone Jack, Reset Switch, confirmation LED lamp
- **Color** : Red
- **Size** : 140 mm. x 40 mm.
- **Weight** : 270 g
- **Joint volume** : DC - 30V 1A.



CL-202

Manual Base



- **Model** : CL-205
- **Material** : ABS
- **Color** : Red
- **Size** : 140 mm. x 50 mm.

CL-205

Single Station Smoke Detector

Combination Smoke & Heat Detector



- **Model** : CL-188
- **Power** : DC 9V Battery
- **Operating Temperature** : 32 ~ 100 °F
- **Relation Humidity** : 0~95% RH
- **Nominal Sens** : 2.3 ± 1.2 % Ft Obscuration
- **Heat sensor set point** : 115 °F
- **Loud 85 dB Piezoelectricity** : Unit "Beeps" every 20 seconds for Min. 7 days to indicate battery need replacing.
- **Alarm Low Battery Warning**
- **Color** : Ivory

CL-188

Fire Alarm Bell 6"

- **Model** : CL-406
- **Input Voltage** : 24V DC
- **Operation Current** : 25 mA
- **Sound Output** : 93dB@1M
- **Movement** : Motor, Pinion and Striker
- **Movement Features** : DC motor, acetral gear wheel, steel striker
- **Gong** : Steel, secured with phillips screw
- **Base Plate** : Molded black polycarbonate
- **Dimension** : 6" (152 mm)
- **Color** : red



CL-406