

Manual Call Point



- **Model** : CL-201
- Operating Power : 24V DC 30mA
- Operating Contact : Max.30V DC 500mA
- Sub-Function : Phone Jack, confirmation LED, reset button.
- Material : Fire-proof plastic
- Dimensions : 140mm(Dia.) x 45mm(H)
- Weight : About 160 g




CL-201

Manual Base



- **Model** : CL-203
 - Material : Plastic
 - Color : Red
 - Size : 140 mm. x 50 mm.
- CL-203**


Alarm Siren / Strobe



CL-207L

- **Model** : CL-207L
- Input Voltage Range : 24V DC (12 ~ 30V DC)
- Operation Current : LED : 50 mA (Max : 65mA)
- Strobe : OVER 8,000m cd. (6pcs Super bright LED)
- Sound Output : 100 +- 5dB (at 24V DC)
- Tone Type : ALARM SIREN (CL-207L)
- Operation Temperature : -10° C~ + 60° C
- Continue Operation Test : OVER 72 Hours (at 24V DC)
- Life Test : "ON" 1 minute, "OFF" 30 seconds, Duty Cycle (at 24V DC) Continuously over 500 Hours period
- Color : Red

Fire Alarm Bell 6"



- **Model** : CL-406
- Input Voltage : 24V DC
- Operation Current : 25 mA
- Sound Output : 93dB@1M
- Movement : Motor, Pinion and Striker
- Movement Features : DC Motor, acetal gear wheel, steel striker
- Gong : Steel, secured with phillips screw
- Base Plate : Molded black polycarbonate
- Color : Red
- Material : Steel plate
- Dimension : Ø 6" (152mm) x 56mm(H)
- Weight : About 850g



CL-406